





RANGE

Indoor compact floodlight with integral gear tray for use with 70W and 150W HQI lamps.

APPLICATIONS

This is a luminaire with low running costs and excellent colour rendering which is particularly suitable for small and medium size indoor areas i.e. shop windows, show rooms, hotels and restaurants.

CONSTRUCTION

Body is made of extruded aluminium, finished in electrostatically applied white or black polyester powder paint producing a very durable finish. The body has a painted steel mounting bracket. The control gear tray is easily removable. The reflector is manufactured with high purity demi-opaque anodized aluminium to maximize light output. The front protection lens is made of toughened glass.

ELECTRICAL





The zinc coated gear tray is supplied with a three poles terminal block. High temperature silicon insulated conductors are used throughout.

OPTIONAL

Special UV filter glass can be provided on request to be used with 150 W HQI lamps.

SPECIFICATION

Designed in accordance with the following Standards: CEI 34-21 and EN60598-1.



ORDERING DATA				
CODE N°		LAMP	LAMP HOLDER	WEIGHT KG
BLACK	WHITE			
NX 3701	NX 3702	EMPTY	R7S-70	0,30
NX 3703	NX 3704	EMPTY	R7S-150	0,30
NX 3711	NX 3751	70 W HQI	R7S	5,50
NX 3713	NX 3753	150 W HQI	R7S	6,50
NX 3790		U.V. FILTER GLASS		0,20