



# MADISON®

RESIDENTIAL

LAMP COMPARTMENT

IP 54 

ELECTRIC COMPARTMENT

IP 54 



## RANGE:

Modern form, mast-mounted luminaires suitable for light up the surroundings without any glare.

The newly developed and elegantly concealed faceted reflector system of the Madison luminaires ensures optimum lighting effect and distribution.

## APPLICATIONS:

Madison is suitable for residential roads, shopping streets, access roads, shopping streets, shopping malls and parking areas. Recommended mounting heights 3-5 m.

Madison can accommodate 70W/150W HQI, 100W/150W MBI and 70W/150W HPS

## CONSTRUCTION:

Body, arms, top and fixing spigot are made of die-cast aluminium.

The top die cast aluminium part is a cover joined to the body through hinged axes and stainless steel locking bolts .

The lower part (spigot) that allow fixing the luminaire to the pole (60/76 mm) is also made of die cast aluminium.

All parts are finished with super thermosetting polyester powder coat paint, 2.5 mil. nominal thickness, applied over a chromate conversion coating; 2500 hours salt spray test endurance rating for outdoor uses.

The optical system is formed by an anodised and faceted high purity (99.85%) aluminium .

The diffuser is made of clear shatterproof (V2) self extinguishing UV stabilized polycarbonate.

## ELECTRICAL:

Control gear plate is placed between the master spigot and upper body easily accessible for maintenance.

## SPECIFICATION

Designed in accordance with the following Standards: CEI 34-21 and EN60598-1

### ORDERING DATA

CODE N°	LAMP	LAMP HOLDER	WEIGHT KG
NX 7410	EMPTY	E27	10,50
NX 7411	EMPTY	R7S-70	10,50
NX 7412	EMPTY	R7S-150	10,50
NX 7413	70W HPS	E27	12,10
NX 7414	70W HQI	R7S	12,10
NX 7415	100W MBI	E27	12,30
NX 7416	150W HQI	R7S	12,40
NX 7417	80W MBF	E27	12,10
NX 7418	125W MBF	E27	12,30